


C2 1175 Appleby Line, Burlington Ontario Canada L7L 5H9 Phone: (905) 332-3271 Fax: (905) 332-9497 Toll: (800) 267-2082 Website: www.phqglobal.com



Hole Sizes and Drill String

1³⁄₈" to 1³⁄₄" 35mm to 44mm 1³⁄₄" to 2¹⁄₈" 45mm to 54mm 2¹/₈" to 2¹/₂" 54mm to 64mm 2¹/₂" to 6"+ 64mm -152mm+ **Drill Shank Size** Shank Seal Size

Drill Statistics

Piston Diameter (Bore) Piston Stroke Compressed Air Consumption Flushing Water Required

Drill Performance Statistics

| Blows per minute Rotation Torque | 1600 @ 73 psi 236 ft/lb @ 73 psi | 1600 @ 5 E 320Nm @ 5 |
|-------------------------------------|-------------------------------------|-------------------------|
| Hose Sizes | | |
| Percussion (Throttle) | 1½ | 38mm |
| Rotation Motor | 1 " | 25mm |
| Air Water Flushing | 3/4" | 20mm |

Recommended Size

1.0" Rope Thread 1.25" Rope Thread 1.5 Rope Thread 1.75 Rope Thread 1 ³⁄₄" x 1 ³⁄₄" x Thread 9/16"

4.49"

3.39"

495 cf/m @ 100 psi

10 G/m @ 70 psi (Max)

Recommended Size

R25 - HM25 - T25 R32 - HM32 – T32 R38 - HM38 - T38 R45 - HM45 - T45 44mm x 44mm x Thread 14mm

| 114mm |
|----------------------|
| 86mm |
| 14 cm/m @ 7 Bar |
| 37 L/m @ 5 Bar (Max) |

Bar 5 Bar

| ISO 9001-2008 | OM | CERT 002485 |
|---------------|----|-------------|
| US SIC 5082 | | NACE 651.6 |