

PHQ36-Independent Rotation Drill

PHQ36-IR Drill

This dependable, powerful pneumatic production rock drill is recommended for long-hole drilling in underground hard rock mining applications.

Fast penetration drilling hole sizes from 38mm to 75mm sizes from 1 ½ inch to 3 inches up to 30 meters in depth up to 100 feet in depth.

www.partshq.com

ISO 9001:2000

Certificate: 002485

Features

Large mating faces on components bodies for less wear and longer life.

Bolt on Front End Cap is available for fast and easy exchange of drill shanks. HOLE SIZE 1.375 - 3.5 in (35 - 89 mm) HOLE DEPTH up to 150 ft (50 meters) REAMING up to 5 inches (130mm)

PHQ36-IR Specifications

CYLINDER BORE

4.49 inches – 114mm

CYLINDER STROKE

3.39 inches – 86mm

FREQUENCY

27 Hz @ 500kPa

ROTATION MOTOR TORQUE @ 120 rpm

240 ft lbs @ 75 psi 320 Nm @ 500 kPa

AIR CONSUMPTION

450cfm @100psi - 212 L/Sec @7 Bar

WATER REQUIREMENTS

10 gpm @ 70 psi - 37 L/Min @ 5 Bar

SHANK SIZE

1³/₄ inch - 44mm Four Spline

DRILL AIR CONN HOSE SIZE

1 ½ inch bsp 1 ½ inch – 38mm

ROTATION AIR CONN HOSE SIZE

1 Inch bsp

1 inch – 25mm

THE PHQ36-IR drill is available mounted on Aluminum Feed assemblies for four foot or six foot drill steel change. The assembly is completed with a PHQ150001H Centralizer and 5 lever PHQ21002 Remote Control Panel

PHQ36-IR Drill



PHQ carries a full range of parts for the PHQ36-IR drill in stock.

All parts made in Canada to precise specifications using only the highest quality tool steel

www.partshq.com