

# PARTS HEADQUARTERS INC.

1175 Appleby Line, Unit C2, Burlington, Ontario, Canada L7L 5H9 Phone 905-332-3271 Fax 905-332-9497 Email info@partshq.com

### JOY AL60M Jackleg

All internal parts in the JOY AL60M Jacklegs are also used in JOY Stopers, and JOY Sinker drills.

Drill delivers high penetration, and powerful torque.

Larger mating faces between major cylinder components for longer life and less wear.


Improved
pusher leg is
available with
a stainless steel
piston rod to prevent
corrosion and pitting.
Positive lubrication with

Positive lubrication with good front end blow.

Convenient operating controls, with push button leg retraction and adjustable motorcycle control feed located on the backhead of the drill

Locking steel retainer for collared steel standard.

Uses rock drill oil or triple zero rock drill grease.



JOY AL60M Jackleg Drill

PHQ's reliable AL60M drills are the jackleg drills of choice in the Sudbury Nickel Mines



ISO 9001:2000

Certificate: 002485 SIC 5082

www.partshq.com

#### **Features**

Large mating faces on components bodies for less wear and longer life

Reduced weight for ease of handling.

#### JOY AL60M Jackleg Specifications

CYLINDER BORE

 $3^{1}I_{8}$  inches – 79.4mm

CYLINDER STROKE

 $2^{1}I_{2}$  inches – 63.5mm

AIR CONSUMPTION

200cfm @90psi - 5.7cu m/m @620kPa

BLOWS PER MINUTE

2250bpm @ 90psi - 2250bpm @620kPa

SHANK SIZE - Collared

71. inch x 41/4 inch - 22mm x 108mm

LENGTH

Drill 22 inches – 559mm Leg Retracted 60 inches – 1530mm Leg Extended 91 inches – 2317mm

WEIGHT

Drill 71 lb - 32kg Leg 30 lb - 14kg


JOY AL60 Jackleg configurations:

☐ JHM Integral steel muffler☐ JHS Standard exhaust

□ L Complete with Leg

AL60JHML Muffled jackleg collared c/w steel retainer & leg

## JOY AL60M Jackleg Drill





PHQ carries a full range of parts for JOY AL60M drills in stock.

Parts made in Canada to precise specifications using only the highest quality tool steel